ZETAENNE SRL



Via L. Settembrini, 41 - 47039 - Savignano sul Rubicone (FC) Tel. +39 (0)543 468781 Fax +39 (0)543 449051 email: info@znled.it - Pec brightmax@pec.it www.znled.it SDI R3KOGSP C.F./P.IVA IT04089040408 Reg. Imprese R.E.A. FO-329237



DECLARATION OF CONFORMITY CE

STRIP LED Ultra Long 10 meters

The company ZetaEnne S.R.L., as manufacturer of lighting fittings, hereby declares, under its own responsibility, that the products below are in conformity to the following EEC directives, changes included and with the relevant national standards:

2014/30/UE	EMC Directive, updates 92/31/EEC and 93/68/EEC
2014/35/UE	Low Voltage Directive
2011/65/UE	Directive on the restriction of the use of hazardous substances in EEA
2009/125/UE	Energy related products

and with the following harmonized standards and/or technical specifications, or parts there of:

IEC 62778:2014 IEC 62717:2014	Application of IEC 62471 for the assessment of blue light hazard to light sources and luminaires LED modules for general lighting - Performance requirements
IEC EN 62031:2008	LED modules for general lighting - Safety specifications
EN 62471:2008	Photobiological safety of lamps and lamp systems
EN 62493:2015	Assessment of lighting equipment related to human exposure to electromagnetic fields
EN 61547:2009	EMC for immunity
EN 50581:2012	Technical documentation for the assessment of the electrical and electronic product with respect to the restriction of hazardous substances
EN 60598-1:2015	Luminaires - Part 1: General Prescriptions and tests
EN 60598-2-1:1989	Luminaires - Part 2: Particular requirements - Section 1: Fixed general purpose luminaires
EN 55015:2013	Limits and methods of measurement of radio disturbances characteristics of electrical lighting and similar equipment.
EN 61000-3-2:2014	Electromagnetic Compatibility (EMC). – Part 3: Limits Section 2: Limits for
	harmonic current emissions (equipment input current of 16 A per phase).
EN 61000-3-3:2013	Electromagnetic Compatibility (EMC) Part3: Limits Section 3: limitation of voltage fluctuation and flicker in low-voltage supply systems for equipment with rated current of 16 A.

SAVIGNANO SUL RUBICONE, lì 08/10/2020

ZETAENNE S.R.L. SCARPELLINIDAVIDE

Demple