

PRODUCT DATA SHEET

LED STRIP ULTRA LONG L068 - 10 meters

Product typology

Flexible high efficiency strip LED with adhesive film

Material technical spec

Flexible PCB support with increased quantity of copper and adhesive film 3M LSE300
 Copper thickness: 3 ounces for reel 10mt

Color: white

Lighting technical spec

LED light source with frontal emission with beam angle of 120°
 60 LED/meter
 10mm PCB, with 0.15M DC female connector at one side, with end cap at another end.
 4.8W/mt 24V 6000k 2835

Wiring technical spec

Driver not included
 The strip can be cutted every 5 cm through the use of scissors

Installation and maintenance technical spec

The strip must be installed on aluminum profile to have a better heat dissipation
 The strip can be installed on aluminum profile (available as accessories) through adhesive film 3M LSE300
 No ordinary maintenance required


Technical spec

- CRI	>80	- Nominal voltage	DC 24 V
- Step McAdam	3	- IP protection	IP20/IP65/IP68
- Lifetime LED	30.000 h@25°C	- n. LED	60 LED/meter
- RG	0	- Colour	6000K
- Beam angle	120°		



Weight/Dimension	LED STRIP IP20	LED STRIP IP65	LED STRIP IP68
Gross weight	- g	- g	- g
Strip dimension	10 meters reel	10 meters reel	10 meters reel
Single package	Antistatic bag	Antistatic bag	Antistatic bag



Photometry

Beam angle 120°

Codice Code	Descrizione prodotto Product description	Potenza Nominale Nominal Power	Temperatura colore Color temperature	Protezione IP IP protection	Flusso apparecchio Luminaire flux	Efficienza apparecchio Luminaire efficiency
S422804830	Strip LED Ultra Long 4,8W 6000K IP68	4,8 W/m	6000 K	IP68	4.990 @ta25°C	104 lm/W

Accessories

Aluminum profile: cod. 65411, 65412, 65413, 65421, 65422

Driver IP20: cod. 650752 (Meanwell), 651502 (Meanwell), 65035, 65060, 65120, 65200, 65250

Driver IP67: cod. 651030, 651060, 651100, 651150, 651250